

ITT

B4NS

Wastewater

Goulds Pumps

4NS Submersible
Sewage Pump
4" Non-Clog Sewage Pump




 **GOULDS PUMPS**

Goulds Pumps is a brand of ITT Corporation.
www.goulds.com

Engineered for life

FEATURES

- **Impeller:** Cast iron, two vane closed design for high efficiency and maximum wear life. Balanced for smooth operation. Optional bronze impeller available.
- **Bronze Wear Ring:** Replaceable to renew the running clearances and efficiencies to original conditions.
- **Casing:** Heavy duty cast iron, volute type for maximum efficiency. 4" 125# ANSI cast iron flanged. Adaptable to guide rail mounting system.
- **Tandem Seals:** Two independently mounted mechanical face type seals are separated by an oil filled chamber. The oil chamber acts as a barrier to trap moisture and provide time for a planned shutdown and maintenance. The oil provides lubrication to the internal (upper) seal. Carbon rotating and ceramic stationary faces are standard on both internal (upper) and external (lower) seals. Optional materials are available for the lower seals. See the Nomenclature Page for order number changes to order either silicon carbide/silicon carbide faces with Viton or silicon carbide/tungsten carbide faces with Viton elastomers. These are recommended for applications containing fine solids or abrasives as found in parking lot/garage drainage and construction dewatering jobs.
- **Moisture Protection System:** Two-wire, dual moisture sensing probes are located in the oil filled chamber between the inner and outer seals. When connected to a control panel with an optional Moisture Detection System and an alarm it will detect the presence of moisture should the outer seal fail. It will also detect moisture in the motor chamber and provide a warning prior to water levels reaching the bearing or stator.
- **Designed for Continuous Operation:** Motor is rated continuous duty submerged condition in water that is 40° C or below. Maximum runtime with pump unsubmerged for 7½–40 HP is 15 minutes. Motor is suitable for 10 starts per hour.
- **Bearings:** Ball, single-row, angular contact, Conrad type bearings with a Class 3 internal fit conforming to AFBMA Standard 20 are used. The bearings are greased for life with a premium moisture resistant polyurea thickened grease containing rust inhibitors and suitable for operation over a range of –25° C to +120° C.
- **Impeller Mounting Screw:** 300 series stainless steel with anti-rotational locking patch.
- **Castings:** All iron castings are ASTM A48 class 30 gray cast iron. Optional bronze impeller is ASTM B584 C87600 silicon bronze.



ITT

GOULDS PUMPS Wastewater

APPLICATIONS

Heavy duty design features for a wide range of commercial and industrial applications such as:

- Sewage systems
- Flood and pollution control
- Industrial dewatering
- Wastewater treatment plants
- Municipal and subdivision lift stations

SPECIFICATIONS

Pump:

- Solids handling capabilities: 3" maximum.
- Discharge size: 4" 125# ANSI flanged.
- Capacities: up to 1160 GPM.
- Total heads: up to 140 feet.
- Minimum flow: 100 GPM.
- Maximum flow: end of published curve.
- Mechanical seals: 304 stainless steel metal parts, BUNA- N elastomers with carbon/rotary and ceramic/stationary faces standard for upper and lower seals. Optional lower seals are available with Viton elastomers and either silicon carbide/silicon carbide or silicon carbide/tungsten carbide faces.
- Fasteners: 300 series stainless steel.

Motor:

- CSA certified motors (Canadian Standards Association).
- Three phase motors only.

NOMENCLATURE DESCRIPTION

1st Character – Discharge Size

4 = 4" 125 # ANSI Discharge Flange

2nd and 3rd Character – Pump Type / Design

NS = Dual Seal Non-Clog Pump with On-Winding Thermal Sensors and Moisture Detection Sensors

4th Character – Mechanical Seals

1 = Standard Seal – the upper seal is carbon/rotary and ceramic/stationary, the lower seal is carbon/rotary with ceramic/stationary with BUNA elastomers and 304 stainless steel metal parts.

3 = Optional Lower Seal – silicon carbide/rotary and silicon carbide/stationary with Viton elastomers and 304 SS metal parts is recommended for applications with fine solids or abrasives.

5 = Optional Lower Seal – silicon carbide/rotary and tungsten carbide/stationary with Viton elastomers and 304 SS metal parts is recommended for applications with fine solids or abrasives.

5th Character – Motor RPM / Hertz

2 = 1750 RPM / 60 Hz 6 = 1450 RPM / 50 Hz

3 = 1150 RPM / 60 Hz

- Available voltages: 200, 230, 400, 460 and 575 volt, 60 Hertz.
- HP Range: 7.5 - 40.
- Motor shaft is a one-piece design of high strength 416 stainless steel.
- All motors are air-filled and designed for continuous duty when fully submerged or for up to 15 minutes operation in air.
- NEMA design "B" with copper windings.
- Class "F" stator winding designed for inverter duty.
- Moisture System: Two wire dual probe monitoring system constantly monitors seal oil chamber and stator housing for moisture. **Note:** control panel must contain an alarm circuit and alarm device.
- Two (2) normally-closed, automatic reset thermostats connected in series and embedded in adjoining phases.
- Power and sensor cords are 25' standard length, 50' available as an option.
- Motors conform to the latest applicable requirements of NEMA, IEEE, ANSI and NEC standards.

NOTICE: Class 10 quick trip overload protection must be provided in control panel.

AGENCY LISTINGS



Tested to UL 778 and CSA 22.2 108 Standards
By Canadian Standards Association
File #LR38549

Goulds Pumps is ISO 9001 Registered.

6th Character – Horsepower

K = 7.5 M = 15 P = 25 R = 40

L = 10 N = 20 Q = 30

7th Character – Voltage / Phase

2 = 200 / 3 4 = 460 / 3 6 = 380/400 / 3

3 = 230 / 3 5 = 575 / 3

8th Character – Impeller Code

A = 11.0" 10 HP 1150 RPM 40 HP 1750 RPM

 20 HP 1450 RPM

B = 10.75" 30 HP 1750 RPM

C = 10.38" 25 HP 1750 RPM

D = 10.12" 7.5 HP 1150 RPM 15 HP 1450 RPM

E = 9.75" 20 HP 1750 RPM

G = 9.00" 15 HP 1750 RPM 10 HP 1450 RPM

K = 8.00" 10 HP 1750 RPM 7.5 HP 1450 RPM

M = 7.50" 7.5 HP 1750 RPM

T = SPECIAL TRIM


9th Character – Cord Length - Power and Sensor Cords

C = 25' standard F = 50' Optional

10th Character – Options

B = Silicon Bronze Impeller E = Epoxy Paint

F = Both Bronze Impeller and Epoxy Paint




ITT

GOULDS PUMPS Wastewater

SERIES 4NS (All ratings at 3 phase, 60 Hz. Consult factory for 3 phase, 50 Hz applications.)

ORDER NUMBER	HP	PHASE	VOLTS	RPM	IMPELLER DIA. (in.)	IMPELLER CODE	S.F. AMPS	SERVICE FACTOR	FULL LOAD AMPS	LOCKED ROTOR AMPS	POWER CABLE SIZE	SENSOR CABLE SIZE	FRAME SIZE	WT (lbs.)
4NS12K2MC	7.5	3	200	1750	7.50	M	27.0	1.15	24.2	183.8	8/4	18/5	210TY	455
4NS12K3MC			230				23.4		21.0	160.0	8/4			
4NS12K4MC			460				11.7		10.5	80.0	8/4			
4NS12K5MC			575				9.4		8.4	64.0	14/4			
4NS12L2KC			10				200		35.6	31.1	186.2			
4NS12L3KC	230				31.0	27.0	162.0		8/4					
4NS12L4KC	460				15.5	13.5	81.0		8/4					
4NS12L5KC	575				12.3	10.8	64.0		14/4					
4NS12M2GC	15		200		54.8	48.2	256.0		6/4					
4NS12M3GC			230		47.8	42.0	222.0		8/4					
4NS12M4GC		460	23.9	21.0	111.0	8/4								
4NS12M5GC		575	19.1	16.8	88.7	10/4								
4NS12N2EC	20	200	74.8	64.4	342.0	4/4								
4NS12N3EC		230	65.0	56.0	298.0	6/4								
4NS12N4EC		460	32.5	28.0	149.0	6/4								
4NS12N5EC		575	26.0	22.4	119.0	10/4								
4NS12P2CC	25	200	83.6	72.5	394.0	2/4								
4NS12P3CC		230	72.8	63.0	342.0	4/4								
4NS12P4CC		460	36.4	31.5	171.0	4/4								
4NS12P5CC		575	29.1	25.2	137.0	8/4								
4NS12Q2BC	30	200	103.2	89.7	472.0	2/4								
4NS12Q3BC		230	89.6	78.0	410.0	2/4								
4NS12Q4BC		460	44.8	39.0	205.0	2/4								
4NS12Q5BC		575	35.8	31.2	164.0	8/4								
4NS12R2AC	40	200	132.8	114.4	600.0	1/0/4								
4NS12R3AC		230	115.4	99.4	522.0	1/4								
4NS12R4AC		460	57.7	49.7	261.0	6/4								
4NS12R5AC		575	46.2	39.8	209.0	8/4								
4NS13K2DC	7.5	3	200	1150	10.12	D	30.4	1.15	26.5	131.6	8/4	18/5	210TY	455
4NS13K3DC			230				26.4		23.0	114.4	10/4			
4NS13K4DC			460				13.2		11.5	57.2	10/4			
4NS13K5DC			575				10.6		9.2	45.8	14/4			
4NS13L2AC			10				200		40.0	35.0	186.0			
4NS13L3AC	230				34.8	30.4	161.0		8/4					
4NS13L4AC	460				17.4	15.2	80.7		8/4					
4NS13L5AC	575				13.9	12.2	64.5		12/4					



ITT

Wastewater

APPLICATION DATA

Maximum Solid Size	3"
Minimum Casing Thickness	5/16"
Casing Corrosion Allowance	1/8"
Maximum Working Pressure	100 PSI
Maximum Submergence	200 feet
Maximum Environmental Temperature	40° C or 104° F ambient conditions.
Maximum Starts Per Hour	Maximum of 10 evenly spaced starts per hour.

CONSTRUCTION DETAILS

Power Cable Type	1/0 / 4, 2/4, 4/4, 6/4, 8/4, 10/4, 12/4 SOW or SOOW (see Model Info).
Control / Sensor Cable / Type	18/5 SOW.
Power Cable and Cap Assembly	Leads have a BUNA N grommet in addition to being epoxy encapsulated.
Power and Control Cable Lengths	25' standard, 50' optional.
Motor Enclosure	Cast iron ASTM A-48 Class 30.
Motor Shaft	Series 416 Stainless steel.
Motor Design	NEMA design "B" with copper windings and designed to withstand 200 psi water pressure at all seal locations. Air-filled NEMA 210TY frame on 7.5, 10, 15 and 20 HP models. Air-filled NEMA 250TYS frame on 25 - 40 HP models.
Motor Insulation Rating	Class "F" insulation.
Motor Thermal Protection	Two (2) normally closed on-winding thermostats open at 320° F (160° C), automatic reset closes at 221° F (105° C).
Motor Overload Protection	Class 10, ambient compensated, quick-trip overload protection must be provided in control panel.
Motor Moisture Protection	Two (2) moisture sensing probes in the oil-filled seal chamber must be connected to a relay in control panel.
Casing	Cast iron ASTM A-48 Class 30.
Impeller	Cast iron ASTM A-48 Class 30 or optional cast bronze ASTM B584 UNS C87600.
Impeller Type	Two vane enclosed design for maximum efficiency.
Casing/Impeller/Wear Ring	Replaceable bronze wear ring.
External Hardware	Stainless steel.

STANDARD PARTS

Ball Bearings	Lubricated for life bearings are designed for a minimum L10 life of 30,000 hours.
210 and 250 Frame	Single row Radial (upper). Single row Thrust (lower).
Mechanical Seals – Standard	Upper Carbon/rotary and ceramic/stationary. Lower Carbon/rotary and ceramic/stationary.
Mechanical Seals – Optional	Lower Silicon carbide/rotary and tungsten carbide/stationary. Lower Silicon carbide/rotary and silicon carbide/stationary.
Standard Motor O-rings	BUNA-N (nitrile)
Seal Chamber Oil	Premium moisture resistant polyurea thickened grease containing rust inhibitors is suitable for operation over a temperature range of - 25° C to + 120° C.



Goolds Pumps and the ITT Engineered Blocks Symbol are registered trademarks and tradenames of ITT Corporation. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

B4NS May, 2008

© 2008 ITT Corporation

Engineered for life

DIMENSIONS

(All dimensions are in inches.
Do not use for construction purposes.)

HP	RPM	"A" Dim. (in.)
7½	1750	41.3
10		
15		
20		
25		
30	1150	46.6
40		
7½		
10		41.3

