

**MOTOR SPECIFICATIONS**

<b>Motor Design</b>	NEMA design B, squirrel cage induction, oil filled, non toxic oil
<b>Motor Type</b>	Enclosed submersible
<b>Insulation Class</b>	Class B, rated at 120° C
<b>Motor Protection</b>	<u>Single Phase:</u> Internal thermal protection with automatic reset. Installer must provide circuit breaker for short circuit protection per N.E.C standards. <u>Three Phase:</u> Installer must provide external motor overload protection device such as a contactor w/ thermal relay, and circuit breaker for short circuit protection per N.E.C. standards.
<b>Service Factor</b>	1.15
<b>Voltage Tolerance</b>	± 10% from name plate rating

**MOTOR DATA, 60Hz**

Model	Phase	Output Power bhp	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Pole/Speed (rpm)
EJ 10W-3	1*	1.0	230	10.0	38	K	4/1750
EJ 10D-3	3**	1.0	208-230	5.5-5.0	22.4-20	K	4/1750
	3**	1.0	460	2.5	10	K	4/1750
	3	1.0	575	2.0	8	K	4/1750

\* Start switch and capacitor integrated into top of pump.

\*\* These three phase motors are tri-voltage, 208/230/460.

**MATERIALS of CONSTRUCTION**

<b>Upper Motor Lid</b>	Cast Iron ASTM A48 Class 30
<b>Motor Housing</b>	Cast Iron ASTM A48 Class 30
<b>Oil Chamber</b>	Cast Iron ASTM A48 Class 30
<b>Volute</b>	Cast Iron ASTM A48 Class 30
<b>Bottom Plate</b>	Cast Iron ASTM A48 Class 30
<b>Impeller</b>	Cast Iron ASTM A48 Class 30
<b>Lifting Bail</b>	AISI 304 Stainless Steel
<b>Oil (motor &amp; oil chamber)</b>	Non-toxic white mineral oil (Marcol 52)
<b>External Hardware</b>	AISI 304 Stainless Steel
<b>O-Rings</b>	Buna-N
<b>Motor Shaft</b>	AISI 420 Stainless Steel
<b>Upper Bearing</b>	Single row ball bearing
<b>Lower Bearing(s)</b>	Single row ball bearing
<b>Upper Shaft Seal (secondary)</b>	Rotating carbon face w/ stationary ceramic face.
<b>Lower Shaft Seal (primary)</b>	Rotating carbon face w/ stationary ceramic face. Includes V-ring lip seal for lower seal protection Option: Silicon Carbide mechanical seal

**DIMENSIONS, WEIGHT, AND MISC.**

<b>Pump weight, lb. (kg)</b>	77 (35) [EJ 10W-3], 70 (32) [EJ 10D-3]
<b>Maximum submergence, ft. (m)</b>	65 (20)
<b>Discharge size, standard</b>	3 inch horizontal
<b>Discharge type</b>	Flange with standard ANSI class 125 bolt pattern
<b>Maximum temp. of pumped fluid</b>	40°C continuous, 50°C intermittent
<b>Agency Approvals</b>	UL 778 and CSA C22.2-108

**CABLE SPECIFICATIONS**

POWER CABLE	VOLTAGE	DIAMETER	LENGTH	OUTER JACKET
14/3 SEOWW (EJ 10W-3)	230	0.36in (9.14mm)	20 ft (6m)	Thermoplastic elastomer
16/4 SEOWW (EJ 10D-2)	208-230/460/575	0.43in (10.9mm)		



