

Products

GA-92XT

Specifications & Features

Features

- Seven Year Warranty
- *Digital readout and expanding bar graph displays signal strength and polarity
- Continuous Gain control, with range indicated by a 4-segment LCD at each quarter turn
- Piezoelectric speaker
- 24-Hours operational life (intermittent usage) on 1 lithium 9-volt battery
- The unit is shipped with two 9-volt lithium batteries. Lithium batteries provide twice the life of alkalines, and have a 10-year shelf life.
- 4-Segment BATT LCD monitors battery charge
- Lightweight, easy-to-use-design reduces search time
- Modular construction; high performance components
- Patented HeliFlux® sensors
- No response to aluminum, brass, or copper
- Y2K compliant

Both the GA-92XTi and the GA-92XTd are standard with a custom case designed to withstand the rigors of field use and a carrying holster.

Specifications

Output

Audio	Signal increases in frequency with gradient-field intensity. Idle frequency = 10 Hz
Visual*	Expanding bar graphs indicate polarity (+ or -) and relative strength (GA-92XTd model only)
Battery Life	24 Hours (intermittent usage)
Input Power	One lithium 9-volt battery
Battery Check	4-segment LCD BATT indicator
Weight	Approximately 2.4 lb. (1.1 kg)
Operating Temp	-13 ^o to 140 ^o F (-25 ^o to 60 ^o C)

Products

GA-92XT

Specifications & Features

Features

Seven Year Warranty

Overall Length	26 in. (~66 cm) (when extended) 15.5 in (~39 cm) (when collapsed)
Waterproof Length	11.5 in. (~29 cm) (when extended)
Nominal Sensor Spacing	9.5 in. (~24 cm)
Construction	30% glass-filled, high impact ABS, .2 in (~5 mm) wall thickness

* Refers to GA-92XTd model only.