

SPECIFICATIONS

Product Description: **VENTILATION BLOWER, HEAVY DUTY**
Part Number: **9502**
Style: **CENTRIFUGAL FAN**

GENERAL DESCRIPTION:

High performance and durability are built into this blower. It's large totally enclosed 1 ½ motor and dual 8" ports, allow high flow allowing positive ventilation or fume extraction. Designed with a large metal base and locking caster wheels, to allow great maneuverability.

CONSTRUCTION:

- 8" Flange on intake and exhaust ports.
- Tough "safety orange" Polyethylene construction.
- One piece housing with integrated handle
- Powder coated 16 gauge steel base and stand
- Steel blower wheel with aluminum hub.
- Steel zinc plated grill
- Equipped with four locking caster wheels.



MOTOR:

Specs: 1 ½ HP, UL Listed, CSA Certified
Voltage: 115V/230 VAC, Single Ø, 60 Hz
Current Draw: 16A (115V)/ 8A (230V)
Start: Dual capacitor.
Switch: Toggle ON/OFF
Cord: 8' SJTW, 14/3 AWG, 90C 300V Medium Duty
Plug: NEMA L5-20P (125V), NEMA L6-20P (230V)

DUCTING: (Optional)

- Retractable, Non-collapsible design
- Single-Ply, PVC coated, vinyl and polyester materials, Temp resistant up to 150° F
- Yellow color with black weather-strip and integrated nylon straps.
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 Specs

BLOWER DIMENSIONS:

Length	Width	Height	Weight
24"	19"	25"	87 Lbs

FLOW RATES: (flow rates meas. with 15' of 8" ducting)

Free Air	One 90° Bend	Two 90° Bends
1700 CFM	1200 CFM	960 CFM