



SPECIFICATIONS

Product Description: **VENTILATION BLOWER, 2-SPEED**
 Part Number: **9507**
 Style: **CENTRIFUGAL FAN**

GENERAL DESCRIPTION:

This blower offers greater flexibility by allowing workers to use high speed in some applications such as purging an area, and the lower speed in other sites such as very dusty environments. The 8" ports allow for positive ventilation or fume extraction. It has a large metal base and with handles integrated for support and portability. Comes complete with in-line GFI for safety.

CONSTRUCTION:

- 8" Flange on intake and exhaust ports.
- Tough "safety orange" polyethylene construction.
- One piece housing with integrated handle
- Powder coated 16 gauge steel base and handles.
- Steel zinc plated grill.
- Equipped with four (4) rubber feet.

MOTOR:

HP: ¾ HP, UL Listed
 Voltage: 115 VAC, 60Hz, single Ø
 Max RPM: 1725 (High Speed), 1140 (Low Speed)
 Current Draw: (High) 10A (Loaded at 115V, 60Hz), (Low) 4A (Loaded at 115V, 60Hz)



GFI CORD::

- Integrated with a NEMA 5-15P Plug
- 14/3 AWG
- 20A, 120V (60Hz)
- 1875 Watts
- 2 feet in length

DIMENSIONS:

Length	Width	Height	Weight
24"	22"	21"	63 Lbs

FLOW RATES: (flow rates meas. with 25' of 8" ducting)

Free Air (High Speed)	One 90° Bend (High Speed)	Two 90° Bends (High Speed)
1850 CFM	1050 CFM	800 CFM
Free Air (Low Speed)	One 90° Bend (Low Speed)	Two 90° Bends (Low Speed)
760 CFM	500 CFM	360 CFM