

# SPECIFICATIONS

Product Description: **VENTILATION BLOWER, ECONOMY**  
Part Number: **9512**  
Style: **CENTRIFUGAL FAN**

## GENERAL DESCRIPTION:

Smart Compact design allows for easy use and storage without sacrificing airflow. Two 8" ports offer positive ventilation or fume extraction. This lightweight unit is only 35 Lbs. Works great with generators. Air delivery certified CEESI.

## CONSTRUCTION:

- 8" Flange on intake and exhaust side.
- Tough "Safety Orange" ABS Housing with integrated handle.
- Black powder coated 16-gauge steel base.
- Steel Fan Wheel with aluminum hub.
- Steel Zinc Plated Grill
- Equipped with four (4) rubber feet.



## MOTOR:

HP: 1/3 HP, UL Listed, and CSA Certified.  
Voltage: 115 VAC Single Ø, 60 Hz  
Max RPM: 3450 (Loaded at 120 Volts, 60 Hz)  
Current Draw: 6A (Loaded at 120 Volts, 60 Hz)  
Cord: 6.5' 16/3 AWG, SJTW-A Thermoplastic 90C 300V Medium Duty  
Plug: NEMA 5-15 Three-prong plug

## DUCTING: (Optional)

- Single-Ply Lightweight Vinyl/polyester, PVC coated.
- 150° F Temp resistant.
- Yellow with black weather stripe.
- Retractable, Non-collapsible design.
- Hard drawn spring steel wire helix,

## DIMENSIONS:

Length	Width	Height	Weight
16"	18.5"	20"	35 Lbs.

## FLOW RATES: (flow rates meas. with 15' of 8" ducting)

Free Air	One 90° Bend	Two 90° Bends
1066 CFM	839 CFM	745 CFM