



SPECIFICATIONS

Product Description: **VENTILATION BLOWER, STANDARD**
Part Number: **9515**
Style: **AXIAL FAN 16"**

GENERAL DESCRIPTION:

For applications requiring a large amount of output. Standard is a ½ HP motor with an efficient six-blade impeller in a rugged metal housing.

CONSTRUCTION:

- Complete unit epoxy powder coated in orange.
- Interchangeable flange for intake or exhaust side mounting.
- 18 gauge cold rolled steel housing
- 10 gauge steel bolted motor base.
- Integrated carrying handles on four sides.
- Steel/Chrome Plated Grill.
- Equipped with four (4) rubber feet.
- Stackable design.
- Can be used with Adaptor Reducer (P/N: 9600-50) to be used with 8" ducting.



MOTOR:

HP: ½ HP, 115V AC 60 Hertz, SingleØ, UL Listed CSA Certified
Max RPM: 3450
Current Draw: 6.3 A
Cord: 6.5' 12/3 AWG, SJTW 90C 300V Medium Duty
Plug: NEMA 5-15 (Grounded three-prong)

FAN:

- Glass Reinforced Polypropylene (PPG) six blade fan, with Aluminum Hub.
- Moving Fan mounted 1⅜" from grill for safety.
- Grill Gap – 5/16"

BLOWER DIMENSIONS:

Length	Width	Height	Weight
14"	18"	18"	53 Lbs.

FLOW RATES: (Flow rates meas. with 15' of 16" ducting)

Free Air	One 90° Bend	Two 90° Bends
3400 CFM	2800 CFM	2300 CFM