

SPECIFICATIONS

Product Description: **VENTILATION BLOWER, HIGH OUTPUT**
Part Number: **9516**
Style: **AXIAL FAN 16"**

GENERAL DESCRIPTION:

For applications requiring a maximum amount of output, it offers the highest output of any of our blowers.

CONSTRUCTION:

- Complete unit epoxy powder coated in "Safety" orange.
- Interchangeable flange for intake and exhaust side mounting.
- 20 Gauge cold rolled steel housing
- Bolted motor mount construction.
- Integrated carrying handles on four sides.
- Steel/chrome plated grill.
- Equipped with four (4) rubber feet.
- Stackable design.



FAN:

- Glass Reinforced Polypropylene (PPG) three blade fan with aluminum hub.
- Moving Fan mounted 1 5/8" from grill for safety.
- Grill Gap – 5/16"

MOTOR:

HP: 2 HP, UL Listed, CSA Certified
Phase: Single
Volts: 115/230 AC 60 Hertz
Max RPM: 3450
Current Draw: 22.8 A @ 115 VAC /11.4A @ 230 VAC
Cord: 12' 12/3 AWG, SJOOW-A Neoprene 300V Medium Duty
Plug: NEMA 5-30P or NEMA 6-30P (Twist Lock type)

BLOWER DIMENSIONS:

Length	Width	Height	Weight
14"	18"	18"	73 Lbs

FLOW RATES: (flow rates meas. with 15' of 16" ducting)

Free Air	One (1) 90 degree bend	Two (2) 90 degree bends
5500 CFM	4950 CFM	4400 CFM

* 9516 Blower is **NOT** to be used with 9600-50 Adapter reducer