




SPECIFICATIONS

Product Description: **8" PLASTIC COM-PAX-IAL BLOWER**
 Part Number: **9533 Series**
 Style: **AXIAL FAN 8" WITH OR WITHOUT CANISTER**

GENERAL DESCRIPTION:

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow. Available as a complete system with built in canister and ducting.

CONSTRUCTION:

- Lightweight, corrosion, UV, and chemical resistant polyethylene housing & canister assembly
 - Durable construction design
 - Super quiet
 - "Safety" orange
 - Available as blower only or complete unit with 15' or 25' of ducting and storage canister
- 
- Canister attaches to intake or output side of blower for suction or ventilation
 - Bottom enclosure to protect electrical components
 - Polypropylene nine blade fan
 - Carry handle molded into blower and canister housing
 - Built in On/Off switch
 - Steel/powder coated grill

MOTOR:

HP: 1/3 HP 115V AC, Single Ø
 Max RPM: 3200 (Loaded at 120 Volts, 60 Hz)
 Cord: 20' AWG
 Switch: ON/OFF switch
 Plug: NEMA 5-15P 125V

DUCTING: (included on 9533-15 and 9533-25 models)

- Single-Ply Lightweight Vinyl/polyester, PVC coated 150° F Temp resistant
- Non-Collapsible Retractable design
- Class 1 hard drawn spring steel wire helix, ASTM 227 Specs
- Yellow with black wear-strip and integrated nylon attachment strap

BLOWER DIMENSIONS:

Blower P/N	Length	Width	Height	Weight
9533	13 ¼"	12"	13 ¾"	17 lbs
9533-15	32"	13 ½"	14 ¾"	33 lbs
9533-25	32"	13 ½"	14 ½"	38 lbs

FLOW RATES: (flow rates meas. with 15' of 8" ducting)

Blower P/N	Free Air	One 90° Bend	Two 90° Bends
9533 Series	979 CFM	768 CFM	592 CFM