

## **SPECIFICATIONS**

Product Description: **BLOWER, COM-PAX-IAL, AC**  
 Part Number: **9534, 9534-15, 9534-25**  
 Style: **AXIAL FAN, COMPACT**

### **GENERAL DESCRIPTION:**

Lightweight and Compact design allows for easy portability without sacrificing performance.

### **CONSTRUCTION:**

- 1) Complete unit epoxy powder coated orange.
- 2) 15 Gauge cold rolled steel housing with welded motor mount construction.
- 3) 20 Gauge steel Canister (Avail. with 15' & 25' Ducting)
- 4) Enclosed wide base for greater stability
- 5) Steel/chrome plated grill
- 6) Carry handle made of 3-ply rubber belting.
- 7) Equipped with four (4) rubber feet.



### **FAN:**

- 1) Glass reinforced Polypropylene (PPG) six blade fan
- 2) Aluminum Hub
- 3) Moving fan mounted 1 5/8" from grill for safety.

### **MOTOR:**

HP: 1/3 HP  
 Volts: 115 AC Single Phase  
 Max RPM: 3200 (Loaded at 120 Volts, 60 Hz)  
 Current Draw: 3.6A (Loaded at 120 Volts, 60 Hz)  
 Capacitor: 7.5 MFD 370V AC  
 Cord: 6' SJOOW 16/3 AWG Neoprene, 300V Medium Duty  
 Plug: NEMA 5-15 125V AC



### **BLOWER DIMENSIONS:**

Type	Part No	Length	Width	Height	Weight
Blower Only	9534	12"	08"	10"	15 Lbs
Blower W/ 15' Duct Canister	9534-15	28"	11"	10"	33 Lbs
Blower w/ 25' Duct Canister	9534-25	28"	11"	10"	39 Lbs

### **FLOW RATES:** (flow rates meas. with 15' of 8" ducting) CEESI Tested

Free Air	One 90° Bend	Two 90° Bends
778 CFM	645 CFM	496 CFM