

SPECIFICATIONS

Product Description: **BLOWER, COM-PAX-IAL, DC**
 Part Number: **9537 9537-15, 9537-25**
 Style: **AXIAL FAN, COMPACT**

GENERAL DESCRIPTION:

Lightweight and Compact design allows for easy portability without sacrificing performance. Powered by a 12-Volt source.

CONSTRUCTION:

- Complete unit epoxy powder coated orange.
- 15 Gauge cold rolled steel housing with welded motor mount construction.
- 20 Gauge steel Canister
- (Avail. with 15' & 25' Ducting)
- Enclosed wide base for greater stability
- Steel/chrome plated grill
- Carry handle made of 3-ply rubber belting.
- Equipped with four (4) rubber feet.



FAN:

- Glass Reinforced Polypropylene (PPG) six blade fan
- Aluminum Hub
- Moving Fan mounted 1⁵/₈" from grill for safety.



MOTOR:

HP: 1/4 HP, 12V DC
 Full Load: 1800 RPM
 Current Draw: 13 A
 Fuse: Inline 25A
 Cord: 15' SJOOW, 16/3 AWG 300V, Neoprene Medium Duty
 Connections: Alligator Clips

BLOWER DIMENSIONS:

Type	Part No	Length	Width	Height	Weight
Blower Only	9537	12"	08"	10"	15 Lbs.
Blower W/ 15' Duct Canister	9537-15	28"	11"	10"	33 Lbs.
Blower w/ 25' Duct Canister	9537-25	28"	11"	10"	39 Lbs.

FLOW RATES: (flow rates meas. with 15' of 8" ducting) CEESI Tested

Free Air	One 90° Bend	Two 90° Bends
950 CFM	725 CFM	525 CFM